

## TYRES

|                 |                    |
|-----------------|--------------------|
| Product group   | Tyres              |
| Item number     | 11066101           |
| Valid tyre size | 205 / 75 R 17.5    |
| LI / SI / PR    | 124 / 122 L, 14 PR |
| TL/TT           | TL                 |
| Brand           | Sailun             |
| Tread pattern   | SDR1               |



 **SAILUN**  
TYRE

## Notes and features

- The Sailun SDR1 is a truck tyre for drive axles for local and regional traffic.
- The widened tread grooves provide good self-cleaning and good grip in all weather conditions.
- A rib runs between the tread blocks for improved rigidity and resulting reduced wear.
- Its wide contact area guarantees very good driving stability with optimum grip.

## Technical Informations

|                              |                    |
|------------------------------|--------------------|
| Item number                  | 11066101           |
| EAN                          | 6959655455090      |
| Valid tyre size              | 205 / 75 R 17.5    |
| LI / SI / PR                 | 124 / 122 L, 14 PR |
| TL/TT                        | TL                 |
| Brand                        | Sailun             |
| Tread pattern                | SDR1               |
| M+S                          | M+S                |
| 3PMSF                        | 3PMSF              |
| Axle position truck          | RA                 |
| Rolling resistance           | E                  |
| Wet grip                     | B                  |
| Rolling noise [db].          | 73                 |
| Rolling noise level          | A                  |
| Antistatic                   | No                 |
| Tyre colour                  | Black              |
| ECE regulation number        | ECE 54,ECE 117     |
| Nettogewicht [kg] (gültig)   | 26,20              |
| Recommended rim size         | 6.00               |
| Permitted rim size           | 6.75               |
| Maximum air pressure [bar].  | 7,50               |
| Section width (mm)           | 205                |
| Outer diameter of tyre [mm]. | 753                |
| Stat. radius (SLR) [mm]      | 353                |
| Rolling circumference [mm].  | 2217               |
| Tread depth (mm)             | 15,0               |

E-Ready

No

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 124 L | 1600               | 120          | Single        | 7,50                     |              |
| 122 L | 1500               | 120          | Twin          | 7,50                     |              |