

TYRES

Product group	Tyres
Item number	11066102
Valid tyre size	205 / 75 R 17.5
LI / SI / PR	124 / 122 M, 14 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SAR1



 **SAILUN**
TYRE

Notes and features

- The Sailun SAR1 is a tyre for steer and trailer axles in regional transport.
- Its extra wide grooves and tread sipes provide good grip on rain-soaked road surfaces.
- The particularly wide and firm tyre shoulder and the robust rubber compound enable slow and even wear.
- Thanks to its flat tread pattern design, the rolling resistance and thus the fuel consumption is reduced.

Technical Informations

Item number	11066102
EAN	6959655465204
Valid tyre size	205 / 75 R 17.5
LI / SI / PR	124 / 122 M, 14 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SAR1
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/TR
Rolling resistance	D
Wet grip	B
Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	25,79
Recommended rim size	6.00
Permitted rim size	6.75
Maximum air pressure [bar].	7,50
Section width (mm)	205
Outer diameter of tyre [mm].	753
Stat. radius (SLR) [mm]	353
Rolling circumference [mm].	2217
Tread depth (mm)	13,0

E-Ready	No
---------	----

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
124 M	1600	130	Single	7,50	
122 M	1500	130	Twin	7,50	