

TYRES

Product group	Tyres
Item number	11066109
Valid tyre size	215 / 75 R 17.5
LI / SI / PR	128 / 126 M, 16 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SAR1



 **SAILUN**
TYRE

Notes and features

- The Sailun SAR1 is a tyre for steer and trailer axles in regional transport.
- Its extra wide grooves and tread sipes provide good grip on rain-soaked road surfaces.
- The particularly wide and firm tyre shoulder and the robust rubber compound enable slow and even wear.
- Thanks to its flat tread pattern design, the rolling resistance and thus the fuel consumption is reduced.

Technical Informations

Item number	11066109
EAN	6959655465228
Valid tyre size	215 / 75 R 17.5
LI / SI / PR	128 / 126 M, 16 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SAR1
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/TR
Rolling resistance	D
Wet grip	B
Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	26,92
Recommended rim size	6.00
Permitted rim size	6.75
Maximum air pressure [bar].	7,50
Section width (mm)	211
Outer diameter of tyre [mm].	767
Stat. radius (SLR) [mm]	359.31
Rolling circumference [mm].	2339
Tread depth (mm)	12,5

E-Ready	No
---------	----

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
128 M	1800	130	Single	7,50	
126 M	1700	130	Twin	7,50	