

TYRES

Product group	Tyres	
Item number	11066112	
Valid tyre size	215 / 75 R 17.5	
LI / SI / PR	126 / 124 M, 14 PR	
TL/TT	TL	
Brand	Sailun	
Tread pattern	SDR1	





Notes and features

- The Sailun SDR1 is a truck tyre for drive axles for local and regional traffic.
- The widened tread grooves provide good self-cleaning and good grip in all weather conditions.
- A rib runs between the tread blocks for improved rigidity and resulting reduced wear.
- Its wide contact area guarantees very good driving stability with optimum grip.



Technical Informations

Item number	11066112
EAN	6959655455106
Valid tyre size	215 / 75 R 17.5
LI / SI / PR	126 / 124 M, 14 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SDR1
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	Е
Wet grip	В
Rolling noise [db].	73
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	29,58
Recommended rim size	6.00
Permitted rim size	6.75
Maximum air pressure [bar].	7,00
Section width (mm)	211
Outer diameter of tyre [mm].	767
Rolling circumference [mm].	2260
Tread depth (mm)	15,0
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
126 M	1700	130	Single	7,00	
124 M	1600	130	Twin	7,00	