

TYRES

Product group	Tyres	
Item number	11066113	
Valid tyre size	215 / 75 R 17.5	
LI / SI / PR	126 / 124 M, 14 PR	
TL/TT	TL	
Brand	Sailun	
Tread pattern	SAR1	





Notes and features

- The Sailun SAR1 is a tyre for steer and trailer axles in regional transport.
- Its extra wide grooves and tread sipes provide good grip on rain-soaked road surfaces.
- The particularly wide and firm tyre shoulder and the robust rubber compound enable slow and even wear.
- Thanks to its flat tread pattern design, the rolling resistance and thus the fuel consumption is reduced.



Technical Informations

Item number	11066113
EAN	6959655465211
Valid tyre size	215 / 75 R 17.5
LI / SI / PR	126 / 124 M, 14 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SAR1
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/TR
Rolling resistance	D
Wet grip	В
Rolling noise [db].	73
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	26,44
Recommended rim size	6.00
Permitted rim size	6.75
Maximum air pressure [bar].	7,00
Section width (mm)	215
Outer diameter of tyre [mm].	767
Rolling circumference [mm].	2260
Tread depth (mm)	12,5
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
126 M	1700	130	Single	7,00	
124 M	1600	130	Twin	7,00	