

## TYRES

Product group	Tyres
Item number	11066114
Valid tyre size	215 / 75 R 17.5
LI / SI / PR	135 / 133 L, 16 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SAR1



 **SAILUN**  
TYRE

## Notes and features

- The Sailun SAR1 is a tyre for steer and trailer axles in regional transport.
- Its extra wide grooves and tread sipes provide good grip on rain-soaked road surfaces.
- The particularly wide and firm tyre shoulder and the robust rubber compound enable slow and even wear.
- Thanks to its flat tread pattern design, the rolling resistance and thus the fuel consumption is reduced.

## Technical Informations

Item number	11066114
EAN	6959655465235
Valid tyre size	215 / 75 R 17.5
LI / SI / PR	135 / 133 L, 16 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SAR1
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/TR
Rolling resistance	D
Wet grip	B
Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117,Vecto Certificate
Nettogewicht [kg] (gültig)	27,02
Recommended rim size	6.00
Permitted rim size	6.75
Maximum air pressure [bar].	8,60
Section width (mm)	215
Outer diameter of tyre [mm].	767
Stat. radius (SLR) [mm]	359.31
Rolling circumference [mm].	2260
Tread depth (mm)	12,5

E-Ready

No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
135 L	2180	120	Single	8,60	
133 L	2060	120	Twin	8,60	