

## TYRES

|                 |                    |
|-----------------|--------------------|
| Product group   | Tyres              |
| Item number     | 11066117           |
| Valid tyre size | 225 / 75 R 17.5    |
| LI / SI / PR    | 129 / 127 M, 16 PR |
| TL/TT           | TL                 |
| Brand           | Sailun             |
| Tread pattern   | SAR1               |



 **SAILUN**  
TYRE

## Notes and features

- The Sailun SAR1 is a tyre for steer and trailer axles in regional transport.
- Its extra wide grooves and tread sipes provide good grip on rain-soaked road surfaces.
- The particularly wide and firm tyre shoulder and the robust rubber compound enable slow and even wear.
- Thanks to its flat tread pattern design, the rolling resistance and thus the fuel consumption is reduced.

## Technical Informations

|                              |                    |
|------------------------------|--------------------|
| Item number                  | 11066117           |
| EAN                          | 6959655472707      |
| Valid tyre size              | 225 / 75 R 17.5    |
| LI / SI / PR                 | 129 / 127 M, 16 PR |
| TL/TT                        | TL                 |
| Brand                        | Sailun             |
| Tread pattern                | SAR1               |
| M+S                          | M+S                |
| 3PMSF                        | 3PMSF              |
| Axle position truck          | FA/TR              |
| Rolling resistance           | D                  |
| Wet grip                     | B                  |
| Rolling noise [db].          | 73                 |
| Rolling noise level          | B                  |
| Antistatic                   | No                 |
| Tyre colour                  | Black              |
| ECE regulation number        | ECE 54,ECE 117     |
| Nettogewicht [kg] (gültig)   | 27,61              |
| Recommended rim size         | 6.75               |
| Permitted rim size           | 7.5                |
| Maximum air pressure [bar].  | 7,25               |
| Section width (mm)           | 225                |
| Outer diameter of tyre [mm]. | 783                |
| Stat. radius (SLR) [mm]      | 366.11             |
| Rolling circumference [mm].  | 2388               |
| Tread depth (mm)             | 12,5               |

---

|         |    |
|---------|----|
| E-Ready | No |
|---------|----|

---

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 129 M | 1850               | 130          | Single        | 7,25                     |              |
| 127 M | 1750               | 130          | Twin          | 7,25                     |              |