

TYRES

Product group	Tyres	
Item number	11066136	
Valid tyre size	245 / 70 R 17.5	
LI / SI / PR	143 / 141 J (146 / 146 F), 18 PR	
TL/TT	TL	
Brand	Sailun	
Tread pattern	SAR1	





Notes and features

- The Sailun SAR1 is a tyre for steer and trailer axles in regional transport.
- Its extra wide grooves and tread sipes provide good grip on rain-soaked road surfaces.
- The particularly wide and firm tyre shoulder and the robust rubber compound enable slow and even wear.
- Thanks to its flat tread pattern design, the rolling resistance and thus the fuel consumption is reduced.



Technical Informations

Item number	11066136		
EAN	6959655465280		
Valid tyre size	245 / 70 R 17.5		
LI / SI / PR	143 / 141 J (146 / 146 F), 18 PR		
TL/TT	TL		
Brand	Sailun		
Tread pattern	SAR1		
M+S	M+S		
3PMSF	3PMSF		
Axle position truck	FA/TR		
Rolling resistance	D		
Wet grip	В		
Rolling noise [db].	73		
Rolling noise level	В		
Antistatic	No		
Tyre colour	Black		
ECE regulation number	ECE 54,ECE 117,Vecto Certificate		
Nettogewicht [kg] (gültig)	32,60		
Recommended rim size	7.50		
Permitted rim size	6,75		
Maximum air pressure [bar].	8,75		
Section width (mm)	245		
Outer diameter of tyre [mm].	789		
Stat. radius (SLR) [mm]	364.36		
Rolling circumference [mm].	2299		
Tread depth (mm)	13,0		

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



E-Ready	No
---------	----

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 J	2725	100	Single	8,75	
146 F	3000	80	Single	8,75	
141 J	2575	100	Twin	8,75	
146 F	3000	80	Twin	8,75	