

TYRES

Product group	Tyres
Item number	11066171
Valid tyre size	225 / 70 R 19.5
LI / SI / PR	128 / 126 L, 14 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SAR1



 **SAILUN**
TYRE

Notes and features

- The Sailun SAR1 is a tyre for steer and trailer axles in regional transport.
- Its extra wide grooves and tread sipes provide good grip on rain-soaked road surfaces.
- The particularly wide and firm tyre shoulder and the robust rubber compound enable slow and even wear.
- Thanks to its flat tread pattern design, the rolling resistance and thus the fuel consumption is reduced.

Technical Informations

Item number	11066171
EAN	6959655465242
Valid tyre size	225 / 70 R 19.5
LI / SI / PR	128 / 126 L, 14 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SAR1
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/TR
Rolling resistance	D
Wet grip	B
Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	29,95
Recommended rim size	6.75
Permitted rim size	6.00
Maximum air pressure [bar].	7,60
Section width (mm)	225
Outer diameter of tyre [mm].	811
Stat. radius (SLR) [mm]	377.88
Rolling circumference [mm].	2461
Tread depth (mm)	12,5

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
128 L	1800	120	Single	7,60	
126 L	1700	120	Twin	7,60	