

TYRES

Product group	Tyres
Item number	11066197
Valid tyre size	265 / 70 R 19.5
LI / SI / PR	143 / 141 J, 18 PR
TL/TT	TL
Brand	Sailun
Tread pattern	STM1



Bohnenkamp
Moving Professionals

 **SAILUN**
TYRE

Notes and features

- The Sailun STM1 is an all-position tyre, preferably used as drive tyre for vehicles in regional traffic.
- The special tread pattern design provides driving stability, excellent self-cleaning and good grip in all weather conditions.
- Its robust tyre shoulder as well as the reinforced bead construction guarantee a long service life.
- Protrusions in the tread grooves ensure particularly slow wear and protect against scratch damages.
- Due to the sturdy tread compound, the tyre is extremely puncture resistant.

Technical Informations

Item number	11066197
EAN	6959655464375
Valid tyre size	265 / 70 R 19.5
LI / SI / PR	143 / 141 J, 18 PR
TL/TT	TL
Brand	Sailun
Tread pattern	STM1
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	D
Wet grip	C
Rolling noise [db].	75
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	40,64
Recommended rim size	7.50
Permitted rim size	8.25
Maximum air pressure [bar].	9,00
Section width (mm)	265
Outer diameter of tyre [mm].	867
Stat. radius (SLR) [mm]	400.98
Rolling circumference [mm].	2525
Tread depth (mm)	16,0

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 J	2725	100	Single	9,00	
141 J	2575	100	Twin	9,00	