

TYRES

Product group	Tyres
Item number	11066202
Valid tyre size	285 / 70 R 19.5
LI / SI / PR	146 / 144 L (144 / 142 M), 16 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SFR1



Bohnenkamp
■ ■ ● Moving Professionals

 **SAILUN**
TYRE

Notes and features

- The Sailun SFR1 is a truck tyre for steer axles for multifunctional use in local and regional traffic.
- The optimised tread compound increases the tyre's service life.
- Its wide tyre shoulder and shoulder groove design ensure low rolling resistance and low fuel consumption.
- The wide tread enables slow and even wear and good handling.

Technical Informations

Item number	11066202
EAN	6959655443127
Valid tyre size	285 / 70 R 19.5
LI / SI / PR	146 / 144 L (144 / 142 M), 16 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SFR1
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	C
Wet grip	C
Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	42,20
Recommended rim size	8.25
Maximum air pressure [bar].	9,00
Section width (mm)	283
Outer diameter of tyre [mm].	895
Stat. radius (SLR) [mm]	412.53
Rolling circumference [mm].	2594
Tread depth (mm)	13,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
146 L	3000	120	Single	9,00	
144 M	2800	130	Single	9,00	
144 L	2800	120	Twin	9,00	
142 M	2650	130	Twin	9,00	