

TYRES

Product group	Tyres
Item number	11066203
Valid tyre size	285 / 70 R 19.5
LI / SI / PR	150 / 148 K, 18 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SAR1



 **SAILUN**
TYRE

Notes and features

- The Sailun SAR1 is a tyre for steer and trailer axles in regional transport.
- Its extra wide grooves and tread sipes provide good grip on rain-soaked road surfaces.
- The particularly wide and firm tyre shoulder and the robust rubber compound enable slow and even wear.
- Thanks to its flat tread pattern design, the rolling resistance and thus the fuel consumption is reduced.

Technical Informations

Item number	11066203
EAN	6959655466171
Valid tyre size	285 / 70 R 19.5
LI / SI / PR	150 / 148 K, 18 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SAR1
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/TR
Rolling resistance	D
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	42,34
Recommended rim size	8.25
Maximum air pressure [bar].	9,00
Section width (mm)	285
Outer diameter of tyre [mm].	895
Stat. radius (SLR) [mm]	413
Rolling circumference [mm].	2594
Tread depth (mm)	13,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
150 K	3350	110	Single	9,00	
148 K	3150	110	Twin	9,00	