Bohnenkamp Moving Professionals

05.02.2025

TYRES

Product group	Tyres
Item number	11066241
Valid tyre size	435 / 50 R 19.5
LI / SI / PR	160 J, 20 PR
TL/TT	TL
Brand	Sailun
Tread pattern	STL1





Notes and features

- The Sailun STL1 is a truck trailer tyre with optimised rolling resistance for extended regional transport and long-distance transport.
- Thanks to its special tread pattern design, the tyre is extremely quiet.
- Its very large contact area ensures slow wear and a long service life for the tyre.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	11066241
EAN	6959655453218
Valid tyre size	435 / 50 R 19.5
LI / SI / PR	160 J, 20 PR
TL/TT	TL
Brand	Sailun
Tread pattern	STL1
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Rolling resistance	В
Wet grip	С
Rolling noise [db].	72
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	69,67
Recommended rim size	14.00
Permitted rim size	15.00
Maximum air pressure [bar].	9,00
Section width (mm)	438
Outer diameter of tyre [mm].	931
Stat. radius (SLR) [mm]	431
Rolling circumference [mm].	2656
Tread depth (mm)	12,5

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



05.02.2025

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 J	4500	100	Single	9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.