

TYRES

Product group	Tyres
Item number	11066241
Valid tyre size	435 / 50 R 19.5
LI / SI / PR	160 J, 20 PR
TL/TT	TL
Brand	Sailun
Tread pattern	STL1



Notes and features

- The Sailun STL1 is a truck trailer tyre with optimised rolling resistance for extended regional transport and long-distance transport.
- Thanks to its special tread pattern design, the tyre is extremely quiet.
- Its very large contact area ensures slow wear and a long service life for the tyre.

Technical Informations

Item number	11066241
EAN	6959655453218
Valid tyre size	435 / 50 R 19.5
LI / SI / PR	160 J, 20 PR
TL/TT	TL
Brand	Sailun
Tread pattern	STL1
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Rolling resistance	B
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	69,67
Recommended rim size	14.00
Permitted rim size	15.00
Maximum air pressure [bar].	9,00
Section width (mm)	438
Outer diameter of tyre [mm].	931
Stat. radius (SLR) [mm]	430.64
Rolling circumference [mm].	2656
Tread depth (mm)	12,5

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 J	4500	100	Single	9,00	