

TYRES

Product group	Tyres
Item number	11066282
Valid tyre size	11 R 22.5
LI / SI / PR	148 / 145 L, 16 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SDR1



Bohnenkamp
■ ■ ● Moving Professionals

 **SAILUN**
TYRE

Notes and features

- The Sailun SDR1 is a truck tyre for drive axles for local and regional traffic.
- The widened tread grooves provide good self-cleaning and good grip in all weather conditions.
- A rib runs between the tread blocks for improved rigidity and resulting reduced wear.
- Its wide contact area guarantees very good driving stability with optimum grip.

Technical Informations

Item number	11066282
EAN	6959655466249
Valid tyre size	11 R 22.5
LI / SI / PR	148 / 145 L, 16 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SDR1
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	E
Wet grip	C
Rolling noise [db].	75
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	57,78
Recommended rim size	8.25
Permitted rim size	7.50
Maximum air pressure [bar].	8,50
Section width (mm)	279
Outer diameter of tyre [mm].	1065
Stat. radius (SLR) [mm]	489.11
Rolling circumference [mm].	3248
Tread depth (mm)	19,5

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 L	3150	120	Single	8,50	
145 L	2900	120	Twin	8,50	