

## TYRES

Product group	Tyres
Item number	11066284
Valid tyre size	11 R 22.5
LI / SI / PR	148 / 145 L, 16 PR
TL/TT	TL
Brand	Sailun
Tread pattern	S815



 **SAILUN**  
TYRE

## Notes and features

- The Sailun S815 is a truck tyre for all axles, mainly for use on building sites.
- Zigzag-shaped circumferential grooves provide good traction and prevent stones from penetrating the tyre.
- The deep shoulder groove reduces heat build-up and increases traction.
- Sidewall guards protect the casing from damages.
- The sturdy rubber compound and high tread pattern depth guarantee a long service life for the tyre.

## Technical Informations

Item number	11066284
EAN	6959655418071
Valid tyre size	11 R 22.5
LI / SI / PR	148 / 145 L, 16 PR
TL/TT	TL
Brand	Sailun
Tread pattern	S815
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	D
Wet grip	C
Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	55,88
Recommended rim size	8.25
Permitted rim size	7.50
Maximum air pressure [bar].	8,50
Section width (mm)	279
Outer diameter of tyre [mm].	1054
Stat. radius (SLR) [mm]	489
Rolling circumference [mm].	3083
Tread depth (mm)	18,0

E-Ready

No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 L	3150	120	Single	8,50	
145 L	2900	120	Twin	8,50	