

TYRES

Product group	Tyres	
Item number	11066296	
Valid tyre size	13 R 22.5	
LI / SI / PR	156 / 150 G, 18 PR	
TL/TT	TL	
Brand	Sailun	
Tread pattern	SDO1	





Notes and features

- The Sailun SDO1 is a truck tyre for drive axles of vehicles used in construction and forestry work.
- Its rough block tread pattern provides very good off-road traction.
- The open tyre shoulder guarantees excellent stability and slow, even wear.
- Due to its high tread pattern depth and the cut-resistant rubber compound, the tyre is very durable.



Technical Informations

Item number	11066296
EAN	6959655469103
Valid tyre size	13 R 22.5
LI / SI / PR	156 / 150 G, 18 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SDO1
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Carcass properties	POR
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	77,42
Recommended rim size	9.75
Permitted rim size	9.00
Maximum air pressure [bar].	8,75
Section width (mm)	330
Outer diameter of tyre [mm].	1136
Stat. radius (SLR) [mm]	521
Tread depth (mm)	23,5
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 G	4000	90	Single	8,75	
150 G	3350	90	Twin	8,75	