

TYRES

| | |
|-----------------|--------------------|
| Product group | Tyres |
| Item number | 11066296 |
| Valid tyre size | 13 R 22.5 |
| LI / SI / PR | 156 / 150 G, 18 PR |
| TL/TT | TL |
| Brand | Sailun |
| Tread pattern | SDO1 |



 **SAILUN**
TYRE

Notes and features

- The Sailun SDO1 is a truck tyre for drive axles of vehicles used in construction and forestry work.
- Its rough block tread pattern provides very good off-road traction.
- The open tyre shoulder guarantees excellent stability and slow, even wear.
- Due to its high tread pattern depth and the cut-resistant rubber compound, the tyre is very durable.

Technical Informations

| | |
|------------------------------|--------------------|
| Item number | 11066296 |
| EAN | 6959655469103 |
| Valid tyre size | 13 R 22.5 |
| LI / SI / PR | 156 / 150 G, 18 PR |
| TL/TT | TL |
| Brand | Sailun |
| Tread pattern | SDO1 |
| M+S | M+S |
| 3PMSF | 3PMSF |
| Axle position truck | RA |
| Carcass properties | POR |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54 |
| Nettogewicht [kg] (gültig) | 77,42 |
| Recommended rim size | 9.75 |
| Permitted rim size | 9.00 |
| Maximum air pressure [bar]. | 8,75 |
| Section width (mm) | 330 |
| Outer diameter of tyre [mm]. | 1136 |
| Stat. radius (SLR) [mm] | 520.56 |
| Tread depth (mm) | 23,5 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 156 G | 4000 | 90 | Single | 8,75 | |
| 150 G | 3350 | 90 | Twin | 8,75 | |