Bohnenkamp Moving Professionals

20.09.2024

TYRES

Product group	Tyres	
Item number	11066300	
Valid tyre size	255 / 70 R 22.5	
LI / SI / PR	140 / 137 M, 16 PR	
TL/TT	TL	
Brand	Sailun	
Tread pattern	S637+	





Notes and features

- The Sailun S637+ is a tyre for steer and trailer axles used in regional transport.
- Its extra wide grooves and tread sipes provide good grip on rain-soaked road surfaces.
- The particularly wide and firm tyre shoulder and the robust rubber compound enable slow and even wear.
- Thanks to its flat tread pattern design, the rolling resistance and thus the fuel consumption is reduced.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	11066300
EAN	6959655429787
Valid tyre size	255 / 70 R 22.5
LI / SI / PR	140 / 137 M, 16 PR
TL/TT	TL
Brand	Sailun
Tread pattern	S637+
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/TR
Rolling resistance	D
Wet grip	C
Rolling noise [db].	73
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	42,50
Recommended rim size	7.50
Permitted rim size	8.25
Maximum air pressure [bar].	8,00
Section width (mm)	255
Outer diameter of tyre [mm].	930
Rolling circumference [mm].	2732
Tread depth (mm)	13,5
E-Ready	No

20.09.2024

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
140 M	2500	130	Single	8,00	
137 M	2300	130	Twin	8,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.