

## TYRES

Product group	Tyres
Item number	11066301
Valid tyre size	255 / 70 R 22.5
LI / SI / PR	140 / 137 M, 16 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SAR1



 **SAILUN**  
TYRE

## Notes and features

- The Sailun SAR1 is a tyre for steer and trailer axles in regional transport.
- Its extra wide grooves and tread sipes provide good grip on rain-soaked road surfaces.
- The particularly wide and firm tyre shoulder and the robust rubber compound enable slow and even wear.
- Thanks to its flat tread pattern design, the rolling resistance and thus the fuel consumption is reduced.

## Technical Informations

Item number	11066301
EAN	6959655466126
Valid tyre size	255 / 70 R 22.5
LI / SI / PR	140 / 137 M, 16 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SAR1
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/TR
Rolling resistance	D
Wet grip	C
Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	42,36
Recommended rim size	7.50
Permitted rim size	8.25
Maximum air pressure [bar].	8,00
Section width (mm)	255
Outer diameter of tyre [mm].	930
Stat. radius (SLR) [mm]	434
Rolling circumference [mm].	2732
Tread depth (mm)	13,5

---

E-Ready	No
---------	----

---

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
140 M	2500	130	Single	8,00	
137 M	2300	130	Twin	8,00	