

## TYRES

|                 |                    |
|-----------------|--------------------|
| Product group   | Tyres              |
| Item number     | 11066312           |
| Valid tyre size | 275 / 70 R 22.5    |
| LI / SI / PR    | 148 / 145 M, 16 PR |
| TL/TT           | TL                 |
| Brand           | Sailun             |
| Tread pattern   | SAR1               |



 **SAILUN**  
TYRE

## Notes and features

- The Sailun SAR1 is a tyre for steer and trailer axles in regional transport.
- Its extra wide grooves and tread sipes provide good grip on rain-soaked road surfaces.
- The particularly wide and firm tyre shoulder and the robust rubber compound enable slow and even wear.
- Thanks to its flat tread pattern design, the rolling resistance and thus the fuel consumption is reduced.

## Technical Informations

|                              |                                  |
|------------------------------|----------------------------------|
| Item number                  | 11066312                         |
| EAN                          | 6959655466157                    |
| Valid tyre size              | 275 / 70 R 22.5                  |
| LI / SI / PR                 | 148 / 145 M, 16 PR               |
| TL/TT                        | TL                               |
| Brand                        | Sailun                           |
| Tread pattern                | SAR1                             |
| M+S                          | M+S                              |
| 3PMSF                        | 3PMSF                            |
| Axle position truck          | FA/TR                            |
| Rolling resistance           | C                                |
| Wet grip                     | C                                |
| Rolling noise [db].          | 71                               |
| Rolling noise level          | A                                |
| Antistatic                   | No                               |
| Tyre colour                  | Black                            |
| ECE regulation number        | ECE 54,ECE 117,Vecto Certificate |
| Nettogewicht [kg] (gültig)   | 46,75                            |
| Recommended rim size         | 8.25                             |
| Permitted rim size           | 7.50, 9.00                       |
| Maximum air pressure [bar].  | 9,00                             |
| Section width (mm)           | 275                              |
| Outer diameter of tyre [mm]. | 958                              |
| Stat. radius (SLR) [mm]      | 445.18                           |
| Rolling circumference [mm].  | 2801                             |
| Tread depth (mm)             | 14,5                             |

E-Ready No

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 148 M | 3150               | 130          | Single        | 9,00                     |              |
| 145 M | 2900               | 130          | Twin          | 9,00                     |              |