

TYRES

Product group	Tyres
Item number	11066318
Valid tyre size	295 / 80 R 22.5
LI / SI / PR	154 / 149 K, 18 PR
TL/TT	TL
Brand	Sailun
Tread pattern	S815



 **SAILUN**
TYRE

Notes and features

- The Sailun S815 is a truck tyre for all axles, mainly for use on building sites.
- Zigzag-shaped circumferential grooves provide good traction and prevent stones from penetrating the tyre.
- The deep shoulder groove reduces heat build-up and increases traction.
- Sidewall guards protect the casing from damages.
- The sturdy rubber compound and high tread pattern depth guarantee a long service life for the tyre.

Technical Informations

Item number	11066318
EAN	8936096303492
Valid tyre size	295 / 80 R 22.5
LI / SI / PR	154 / 149 K, 18 PR
TL/TT	TL
Brand	Sailun
Tread pattern	S815
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	D
Wet grip	C
Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	61,03
Recommended rim size	9.00
Permitted rim size	8.25
Maximum air pressure [bar].	8,50
Section width (mm)	298
Outer diameter of tyre [mm].	1044
Stat. radius (SLR) [mm]	486.56
Rolling circumference [mm].	3184
Tread depth (mm)	17,0

E-Ready No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 K	3750	110	Single	8,50	
149 K	3250	110	Twin	8,50	