

TYRES

| Product group | Tyres | |
|-----------------|--------------------|--|
| Item number | 11066323 | |
| Valid tyre size | 295 / 80 R 22.5 | |
| LI / SI / PR | 152 / 148 M, 16 PR | |
| TL/TT | TL | |
| Brand | Sailun | |
| Tread pattern | SDL1 | |





Notes and features

- The Sailun SDL1 is a truck tyre for drive axles for long-haul transport.
- Its tread pattern with 3 circumferential main grooves provides very good stability and ride comfort.
- Narrow, horizontal grooves reduce noise emission and increase drive efficiency.
- The big contact area with the road increases driving stability with a very long service life.



Technical Informations

| Item number | 11066323 |
|------------------------------|--------------------|
| EAN | 6959655454963 |
| Valid tyre size | 295 / 80 R 22.5 |
| LI / SI / PR | 152 / 148 M, 16 PR |
| TL/TT | TL |
| Brand | Sailun |
| Tread pattern | SDL1 |
| M+S | M+S |
| 3PMSF | 3PMSF |
| Axle position truck | RA |
| Rolling resistance | D |
| Wet grip | С |
| Rolling noise [db]. | 75 |
| Rolling noise level | В |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54,ECE 117 |
| Nettogewicht [kg] (gültig) | 65,17 |
| Recommended rim size | 9.00 |
| Permitted rim size | 8.25 |
| Maximum air pressure [bar]. | 8,50 |
| Section width (mm) | 298 |
| Outer diameter of tyre [mm]. | 1044 |
| Stat. radius (SLR) [mm] | 486.56 |
| Rolling circumference [mm]. | 3058 |
| Tread depth (mm) | 17,0 |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



| E-Ready | No |
|---------|----|
|---------|----|

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 152 M | 3550 | 130 | Single | 8,50 | |
| 148 M | 3150 | 130 | Twin | 8,50 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.