# Bohnenkamp Moving Professionals

05.02.2025

#### TYRES

Product group	Tyres	
Item number	11066326	
Valid tyre size	295 / 80 R 22.5	
LI / SI / PR	152 / 149 L, 18 PR	
TL/TT	TL	
Brand	Sailun	
Tread pattern	SW02	



#### Notes and features

- The Sailun SW02 is a truck winter tyre for drive axles with long-life rubber compound.
- The tread pattern with wide grooves and zigzag-shaped sipes reliably deflects water and snow.
- The arrangement of tread pattern blocks and grooves as well as the slip-resistant tread provide excellent handling in wintry conditions.
- The tyre offers very good traction, particularly on snow and ice.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

# Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	11066326
EAN	6959655413038
Valid tyre size	295 / 80 R 22.5
LI / SI / PR	152 / 149 L, 18 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SW02
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	D
Wet grip	D
Rolling noise [db].	73
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	66,79
Recommended rim size	9.00
Permitted rim size	8.25
Maximum air pressure [bar].	9,00
Section width (mm)	298
Outer diameter of tyre [mm].	1050
Rolling circumference [mm].	3058
Tread depth (mm)	20,5
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 L	3550	120	Single	9,00	
149 L	3250	120	Twin	9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.