

TYRES

Product group	Tyres	
Item number	11066329	
Valid tyre size	295 / 80 R 22.5	
LI / SI / PR	152 / 148 M, 16 PR	
TL/TT	TL	
Brand	Sailun	
Tread pattern	SAW1	





Notes and features

- The Sailun SAW1 is a truck winter tyre for steering axles but is also suitable for trailers.
- The wide tread pattern and the tread pattern with 5 main grooves enable very good and safe handling on snow and ice.
- Jagged sipes increase the contact area with the road and enhance the grip.
- The sipe design and the shoulder grooves open on the sides reliably deflect water and snow.
- The special rubber compound keeps its positive characteristics even at low temperatures.



Technical Informations

Item number	11066329
EAN	6959655468960
Valid tyre size	295 / 80 R 22.5
LI / SI / PR	152 / 148 M, 16 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SAW1
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	Е
Wet grip	С
Rolling noise [db].	74
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	63,13
Recommended rim size	9.00
Permitted rim size	8.25
Maximum air pressure [bar].	8,50
Section width (mm)	295
Outer diameter of tyre [mm].	1044
Stat. radius (SLR) [mm]	486.56
Rolling circumference [mm].	3058
Tread depth (mm)	16,5

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



E-Ready No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 M	3550	130	Single	8,50	
148 M	3150	130	Twin	8,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.