

TYRES

Product group	Tyres	
Item number	11066330	
Valid tyre size	295 / 80 R 22.5	
LI / SI / PR	152 / 149 K, 18 PR	
TL/TT	TL	
Brand	Sailun	
Tread pattern	CITYCONVOY	





Notes and features

- The Sailun CITYCONVOY is an all-position truck tyre for regional and long-distance transport.
- The reinforced sidewall protects the tyre from damages caused by kerbs and from premature wear due to repeated starting and stopping in city traffic.
- The sipe design increases the contact area with the road for better grip and driving safety.
- The optimised tread pattern, the particularly hard-wearing rubber compound and high tread pattern depth guarantee a long service life.
- The shoulder notch prevents the tyre from heating up and increases durability.



Technical Informations

Item number	11066330
EAN	6959655436662
Valid tyre size	295 / 80 R 22.5
LI / SI / PR	152 / 149 K, 18 PR
TL/TT	TL
Brand	Sailun
Tread pattern	CITYCONVOY
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	D
Wet grip	С
Rolling noise [db].	72
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	63,90
Recommended rim size	9.00
Permitted rim size	8.25
Maximum air pressure [bar].	9,00
Section width (mm)	295
Outer diameter of tyre [mm].	1044
Stat. radius (SLR) [mm]	486.56
Rolling circumference [mm].	3184
Tread depth (mm)	17,5

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



E-Ready No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 K	3550	110	Single	9,00	
149 K	3250	110	Twin	9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.