# Bohnenkamp Moving Professionals

20.09.2024

### TYRES

Product group	Tyres
Item number	11066337
Valid tyre size	315 / 60 R 22.5
LI / SI / PR	152 / 148 L, 18 PR
TL/TT	TL
Brand	Sailun
Tread pattern	S701





#### Notes and features

- The Sailun S701 is a truck tyre for drive axles for longhaul transport.
- Three wide circumferential tread grooves and the large contact area ensure excellent driving stability and comfort.
- Narrow transverse grooves reduce noise emissions.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	11066337
EAN	6959655406191
Valid tyre size	315 / 60 R 22.5
LI / SI / PR	152 / 148 L, 18 PR
TL/TT	TL
Brand	Sailun
Tread pattern	S701
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	D
Wet grip	С
Rolling noise [db].	75
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	60,59
Recommended rim size	9.75
Permitted rim size	9.00
Maximum air pressure [bar].	9,00
Section width (mm)	315
Outer diameter of tyre [mm].	950
Stat. radius (SLR) [mm]	444.72
Rolling circumference [mm].	2879
Tread depth (mm)	18,0

20.09.2024

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

20.09.2024

E-Ready

No

#### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 L	3550	120	Single	9,00	
148 L	3150	120	Twin	9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.