

## TYRES

Product group	Tyres
Item number	11066338
Valid tyre size	315 / 60 R 22.5
LI / SI / PR	152 / 148 L, 18 PR
TL/TT	TL
Brand	Sailun
Tread pattern	S629



## Notes and features

- The Sailun S629 is a truck tyre for steer axles for multifunctional use in local and regional traffic.
- The optimised tread compound increases the tyre's service life.
- Its wide tyre shoulder and shoulder groove design ensure low rolling resistance and low fuel consumption.
- The wide tread enables slow and even wear and good handling.

## Technical Informations

Item number	11066338
EAN	6959655406184
Valid tyre size	315 / 60 R 22.5
LI / SI / PR	152 / 148 L, 18 PR
TL/TT	TL
Brand	Sailun
Tread pattern	S629
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	C
Wet grip	B
Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	56,05
Recommended rim size	9.75
Permitted rim size	9.00
Maximum air pressure [bar].	9,00
Section width (mm)	315
Outer diameter of tyre [mm].	950
Stat. radius (SLR) [mm]	445
Rolling circumference [mm].	2879
Tread depth (mm)	14,5

E-Ready

No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 L	3550	120	Single	9,00	
148 L	3150	120	Twin	9,00	