

TYRES

Product group	Tyres
Item number	11066339
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	156 / 153 K, 20 PR
TL/TT	TL
Brand	Sailun
Tread pattern	S913A



 **SAILUN**
TYRE

Notes and features

- The Sailun S913A is a truck tyre for drive axles for on- and off-road applications.
- The rough, deep, non-directional tread pattern design and the robust rubber compound provide good traction and a long service life for the tyre.
- Angled tread pattern grooves prevent damages caused by stone penetration.
- The strong casing construction and reinforced tread pattern blocks prevent cut damages and premature wear.

Technical Informations

Item number	11066339
EAN	6959655438628
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	156 / 153 K, 20 PR
TL/TT	TL
Brand	Sailun
Tread pattern	S913A
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Carcass properties	POR
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	75,60
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	8,50
Section width (mm)	315
Outer diameter of tyre [mm].	1076
Stat. radius (SLR) [mm]	500.16
Rolling circumference [mm].	3141
Tread depth (mm)	21,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 K	4000	110	Single	8,50	
153 K	3650	110	Twin	8,50	