

TYRES

Product group	Tyres	
Item number	11066340	
Valid tyre size	315 / 70 R 22.5	
LI / SI / PR	154 / 150 L (152 / 148 M), 18 PR	
TL/TT	TL	
Brand	Sailun	
Tread pattern	SDL1	





Notes and features

- The Sailun SDL1 is a truck tyre for drive axles for long-haul transport.
- Its tread pattern with 3 circumferential main grooves provides very good stability and ride comfort.
- Narrow, horizontal grooves reduce noise emission and increase drive efficiency.
- The big contact area with the road increases driving stability with a very long service life.



Technical Informations

Item number	11066340		
EAN	6959655454987		
Valid tyre size	315 / 70 R 22.5		
LI / SI / PR	154 / 150 L (152 / 148 M), 18 PR		
TL/TT	TL		
Brand	Sailun		
Tread pattern	SDL1		
3PMSF	3PMSF		
Axle position truck	RA		
Rolling resistance	D		
Wet grip	С		
Rolling noise [db].	75		
Rolling noise level	В		
Antistatic	No		
Tyre colour	Black		
ECE regulation number	ECE 54,ECE 117		
Nettogewicht [kg] (gültig)	66,37		
Recommended rim size	9.00		
Permitted rim size	9.75		
Maximum air pressure [bar].	9,00		
Section width (mm)	312		
Outer diameter of tyre [mm].	1014		
Stat. radius (SLR) [mm]	468.28		
Rolling circumference [mm].	2945		
Tread depth (mm)	18,0		
E-Ready	No		

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 L	3750	120	Single	9,00	
152 M	3550	130	Single	9,00	
150 L	3350	120	Twin	9,00	
148 M	3150	130	Twin	9,00	