

## **TYRES**

Product group	Tyres	
Item number	11066341	
Valid tyre size	e size 315 / 70 R 22.5	
LI / SI / PR	154 / 150 L (152 / 148 M), 18 PR	
TL/TT	TL	
Brand	Sailun	
Tread pattern	SDR1	





## Notes and features

- The Sailun SDR1 is a truck tyre for drive axles for local and regional traffic.
- The widened tread grooves provide good self-cleaning and good grip in all weather conditions.
- A rib runs between the tread blocks for improved rigidity and resulting reduced wear.
- Its wide contact area guarantees very good driving stability with optimum grip.



## **Technical Informations**

Item number	11066341		
EAN	6959655455021		
Valid tyre size	315 / 70 R 22.5		
LI / SI / PR	154 / 150 L (152 / 148 M), 18 PR		
TL/TT	TL		
Brand	Sailun		
Tread pattern	SDR1		
M+S	M+S		
3PMSF	3PMSF		
Axle position truck	RA		
Rolling resistance	Е		
Wet grip	С		
Rolling noise [db].	75		
Rolling noise level	В		
Antistatic	No		
Tyre colour	Black		
ECE regulation number	ECE 54,ECE 117		
Nettogewicht [kg] (gültig)	66,44		
Recommended rim size	9.00		
Permitted rim size	9.75		
Maximum air pressure [bar].	9,00		
Section width (mm)	312		
Outer diameter of tyre [mm].	1014		
Stat. radius (SLR) [mm]	468.28		
Rolling circumference [mm].	2945		
Tread depth (mm)	20,0		

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



E-Ready	No
---------	----

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 L	3750	120	Single	9,00	
152 M	3550	130	Single	9,00	
150 L	3350	120	Twin	9,00	
148 M	3150	130	Twin	9,00	