

## TYRES

Product group	Tyres
Item number	11066342
Valid tyre size	315 / 70 R 22.5
LI / SI / PR	154 / 150 L, 18 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SFR1



Bohnenkamp  
■ ■ ● Moving Professionals

 **SAILUN**  
TYRE

## Notes and features

- The Sailun SFR1 is a truck tyre for steer axles for multifunctional use in local and regional traffic.
- The optimised tread compound increases the tyre's service life.
- Its wide tyre shoulder and shoulder groove design ensure low rolling resistance and low fuel consumption.
- The wide tread enables slow and even wear and good handling.

## Technical Informations

Item number	11066342
EAN	6959655445787
Valid tyre size	315 / 70 R 22.5
LI / SI / PR	154 / 150 L, 18 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SFR1
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	C
Wet grip	B
Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	62,22
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	9,00
Section width (mm)	312
Outer diameter of tyre [mm].	1014
Rolling circumference [mm].	2945
Tread depth (mm)	15,5
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 L	3750	120	Single	9,00	
150 L	3350	120	Twin	9,00	