Bohnenkamp Moving Professionals

TYRES

| Product group | Tyres | |
|-----------------|----------------------------------|--|
| Item number | 11066343 | |
| Valid tyre size | 315 / 70 R 22.5 | |
| LI / SI / PR | 154 / 150 L (152 / 148 M), 18 PR | |
| TL/TT | TL | |
| Brand | Sailun | |
| Tread pattern | SW02 | |



Notes and features

- The Sailun SW02 is a truck winter tyre for drive axles with • long-life rubber compound.
- The tread pattern with wide grooves and zigzag-shaped • sipes reliably deflects water and snow.
- The arrangement of tread pattern blocks and grooves as . well as the slip-resistant tread provide excellent handling in wintry conditions.
- The tyre offers very good traction, particularly on snow • and ice.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

| Item number | 11066343 | | |
|------------------------------|----------------------------------|--|--|
| EAN | 6959655419641 | | |
| Valid tyre size | 315 / 70 R 22.5 | | |
| LI / SI / PR | 154 / 150 L (152 / 148 M), 18 PR | | |
| TL/TT | TL | | |
| Brand | Sailun | | |
| Tread pattern | SW02 | | |
| M+S | M+S | | |
| 3PMSF | 3PMSF | | |
| Axle position truck | RA | | |
| Rolling resistance | D | | |
| Wet grip | D | | |
| Rolling noise [db]. | 73 | | |
| Antistatic | No | | |
| Tyre colour | Black | | |
| ECE regulation number | ECE 54,ECE 117 | | |
| Nettogewicht [kg] (gültig) | 66,54 | | |
| Recommended rim size | 9.00 | | |
| Permitted rim size | 9.75 | | |
| Maximum air pressure [bar]. | 9,00 | | |
| Section width (mm) | 312 | | |
| Outer diameter of tyre [mm]. | 1022 | | |
| Rolling circumference [mm]. | 2945 | | |
| Tread depth (mm) | 20,5 | | |
| E-Ready | No | | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 154 L | 3750 | 120 | Single | 9,00 | |
| 152 M | 3550 | 130 | Single | 9,00 | |
| 150 L | 3350 | 120 | Twin | 9,00 | |
| 148 M | 3150 | 130 | Twin | 9,00 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.