

TYRES

Product group	Tyres
Item number	11066347
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	156 / 150 G (154 / 150 J), 18 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SDO1



**SAILUN**
TYRE

Notes and features

- The Sailun SDO1 is a truck tyre for drive axles of vehicles used in construction and forestry work.
- Its rough block tread pattern provides very good off-road traction.
- The open tyre shoulder guarantees excellent stability and slow, even wear.
- Due to its high tread pattern depth and the cut-resistant rubber compound, the tyre is very durable.

Technical Informations

Item number	11066347
EAN	6959655473810
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	156 / 150 G (154 / 150 J), 18 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SDO1
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Carcass properties	POR
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	73,46
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	8,50
Section width (mm)	315
Outer diameter of tyre [mm].	1082
Stat. radius (SLR) [mm]	500.16
Rolling circumference [mm].	3141
Tread depth (mm)	23,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 G	4000	90	Single	8,50	
154 J	3750	100	Single	8,50	
150 G	3350	90	Twin	8,50	
150 J	3350	100	Twin	8,50	