# Bohnenkamp Moving Professionals

### **TYRES**

Product group	Tyres	
Item number	11066349	
Valid tyre size	315 / 80 R 22.5	
LI / SI / PR	156 / 150 L (154 / 150 M), 18 PR	
TL/TT	TL	
Brand	Sailun	
Tread pattern	S815	



#### Notes and features

- The Sailun S815 is a truck tyre for all axles, mainly for use • on building sites.
- Zigzag-shaped circumferential grooves provide good • traction and prevent stones from penetrating the tyre.
- The deep shoulder groove reduces heat build-up and . increases traction.
- Sidewall guards protect the casing from damages. •
- The sturdy rubber compound and high tread pattern depth guarantee a long service life for the tyre.

# Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	11066349	
EAN	6959655421286	
Valid tyre size	315 / 80 R 22.5	
LI / SI / PR	156 / 150 L (154 / 150 M), 18 PR	
TL/TT	TL	
Brand	Sailun	
Tread pattern	S815	
M+S	M+S	
3PMSF	3PMSF	
Axle position truck	FA/RA/TR	
Rolling resistance	D	
Wet grip	C	
Rolling noise [db].	73	
Rolling noise level	В	
Antistatic	No	
Tyre colour	Black	
ECE regulation number	ECE 54,ECE 117	
Nettogewicht [kg] (gültig)	66,66	
Recommended rim size	9.00	
Permitted rim size	9.75	
Maximum air pressure [bar].	8,50	
Section width (mm)	315	
Outer diameter of tyre [mm].	1076	
Stat. radius (SLR) [mm]	500	
Rolling circumference [mm].	3141	
Tread depth (mm)	17,0	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

E-Ready

No

#### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 L	4000	120	Single	8,50	
154 M	3750	130	Single	8,50	
150 L	3350	120	Twin	8,50	
150 M	3350	130	Twin	8,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.