

TYRES

Product group	Tyres
Item number	11066356
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	156 / 150 L (154 / 150 M), 18 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SFR1



Bohnenkamp
■ ■ ● Moving Professionals

 **SAILUN**
TYRE

Notes and features

- The Sailun SFR1 is a truck tyre for steer axles for multifunctional use in local and regional traffic.
- The optimised tread compound increases the tyre's service life.
- Its wide tyre shoulder and shoulder groove design ensure low rolling resistance and low fuel consumption.
- The wide tread enables slow and even wear and good handling.

Technical Informations

Item number	11066356
EAN	6959655443110
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	156 / 150 L (154 / 150 M), 18 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SFR1
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	C
Wet grip	B
Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	70,01
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	8,50
Section width (mm)	312
Outer diameter of tyre [mm].	1076
Stat. radius (SLR) [mm]	500.16
Rolling circumference [mm].	3141
Tread depth (mm)	16,0

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 L	4000	120	Single	8,50	
154 M	3750	130	Single	8,50	
150 L	3350	120	Twin	8,50	
150 M	3350	130	Twin	8,50	