

TYRES

| Product group | Tyres | |
|-----------------|----------------------------------|--|
| Item number | 11066358 | |
| Valid tyre size | 315 / 80 R 22.5 | |
| LI / SI / PR | 156 / 150 L (154 / 150 M), 18 PR | |
| TL/TT | TL | |
| Brand | Sailun | |
| Tread pattern | SW05 | |





Notes and features

- The Sailun SW05 is a truck winter tyre for drive axles for high traction requirements.
- Its groove design provides a large contact area and thus good grip and slip resistance in wintry conditions.
- The grooves and sipes consequently drain off snow and ensure safe driving on snow and ice.
- The special, cold-resistant rubber compound retains its positive characteristics, even at very low temperatures.



Technical Informations

| Item number | 11066358 | | |
|------------------------------|----------------------------------|--|--|
| EAN | 6959655428315 | | |
| Valid tyre size | 315 / 80 R 22.5 | | |
| LI / SI / PR | 156 / 150 L (154 / 150 M), 18 PR | | |
| TL/TT | TL | | |
| Brand | Sailun | | |
| Tread pattern | SW05 | | |
| M+S | M+S | | |
| 3PMSF | 3PMSF | | |
| Axle position truck | RA | | |
| Rolling resistance | E | | |
| Wet grip | D | | |
| Rolling noise [db]. | 75 | | |
| Antistatic | No | | |
| Tyre colour | Black | | |
| ECE regulation number | ECE 54,ECE 117 | | |
| Nettogewicht [kg] (gültig) | 72,34 | | |
| Recommended rim size | 9.00 | | |
| Permitted rim size | 9.75 | | |
| Maximum air pressure [bar]. | 8,50 | | |
| Section width (mm) | 312 | | |
| Outer diameter of tyre [mm]. | 1082 | | |
| Rolling circumference [mm]. | 3141 | | |
| Tread depth (mm) | 22,0 | | |
| E-Ready | No | | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 156 L | 4000 | 120 | Single | 8,50 | |
| 154 M | 3750 | 130 | Single | 8,50 | |
| 150 L | 3350 | 120 | Twin | 8,50 | |
| | | | | 8,50 | |