

TYRES

Product group	Tyres
Item number	11066371
Valid tyre size	385 / 55 R 22.5
LI / SI / PR	160 K (158 L), 20 PR
TL/TT	TL
Brand	Sailun
Tread pattern	STL1



 **SAILUN**
TYRE

Notes and features

- The Sailun STL1 is a truck trailer tyre with optimised rolling resistance for extended regional transport and long-distance transport.
- Thanks to its special tread pattern design, the tyre is extremely quiet.
- Its very large contact area ensures slow wear and a long service life for the tyre.

Technical Informations

Item number	11066371
EAN	6959655463446
Valid tyre size	385 / 55 R 22.5
LI / SI / PR	160 K (158 L), 20 PR
TL/TT	TL
Brand	Sailun
Tread pattern	STL1
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Rolling resistance	B
Wet grip	B
Rolling noise [db].	72
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	67,45
Recommended rim size	12.25
Permitted rim size	11.75
Maximum air pressure [bar].	9,00
Section width (mm)	386
Outer diameter of tyre [mm].	996
Stat. radius (SLR) [mm]	464.04
Rolling circumference [mm].	2933
Tread depth (mm)	12,5

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 K	4500	110	Single	9,00	
158 L	4250	120	Single	9,00	