Bohnenkamp Moving Professionals

TYRES

| Product group | Tyres | |
|-----------------|----------------------|--|
| Item number | 11066375 | |
| Valid tyre size | 385 / 65 R 22.5 | |
| LI / SI / PR | 160 K (158 L), 20 PR | |
| TL/TT | TL | |
| Brand | Sailun | |
| Tread pattern | S825 | |



Notes and features

- The Sailun S825 is a truck tyre for all axles.
- The optimised tread compound increases the tyre's service life.
- Its special shoulder design and the wide tread provide • good stability.
- Stone ejectors in the circumferential tread ribs prevent • tyre damage caused by the penetration of small stones.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

| Item number | 11066375 |
|------------------------------|----------------------|
| EAN | 6959655420746 |
| Valid tyre size | 385 / 65 R 22.5 |
| LI / SI / PR | 160 K (158 L), 20 PR |
| TL/TT | TL |
| Brand | Sailun |
| Tread pattern | S825 |
| M+S | M+S |
| 3PMSF | 3PMSF |
| Axle position truck | FA/RA/TR |
| Rolling resistance | D |
| Wet grip | В |
| Rolling noise [db]. | 72 |
| Rolling noise level | В |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54,ECE 117 |
| Nettogewicht [kg] (gültig) | 77,00 |
| Recommended rim size | 11.75 |
| Maximum air pressure [bar]. | 9,00 |
| Section width (mm) | 385 |
| Outer diameter of tyre [mm]. | 1072 |
| Stat. radius (SLR) [mm] | 495.96 |
| Rolling circumference [mm]. | 3103 |
| Tread depth (mm) | 16,5 |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 160 K | 4500 | 110 | Single | 9,00 | |
| 158 L | 4250 | 120 | Single | 9,00 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.