

TYRES

Product group	Tyres	
Item number	11066385	
Valid tyre size	385 / 65 R 22.5	
LI / SI / PR	160 K (158 L), 20 PR	
TL/TT	TL	
Brand	Sailun	
Tread pattern	STR1	





Notes and features

- The Sailun STR1 is a truck tyre for trailer axles for local and regional use.
- The 4 circumferential tread pattern grooves provide very good handling and ride comfort.
- Crosswise block grooves in the flex tread allow for better grip and slip resistance.
- The wide tyre shoulder prevents premature wear and improves the tyre's service life.



Technical Informations

Item number	11066385
EAN	4040658097072
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	160 K (158 L), 20 PR
TL/TT	TL
Brand	Sailun
Tread pattern	STR1
M+S	M+S
Axle position truck	TR
Rolling resistance	С
Wet grip	С
Rolling noise [db].	71
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	78,19
Recommended rim size	11.75
Permitted rim size	12.25
Maximum air pressure [bar].	9,00
Section width (mm)	389
Outer diameter of tyre [mm].	1072
Rolling circumference [mm].	3103
Tread depth (mm)	16,0
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 K	4500	110	Single	9,00	
158 L	4250	120	Single	9,00	