

TYRES

Product group	Tyres	
Item number	11066388	
Valid tyre size	385 / 65 R 22.5	
LI / SI / PR	160 K (158 L), 20 PR	
TL/TT	TL	
Brand	Sailun	
Tread pattern	SAW1	





Notes and features

- The Sailun SAW1 is a truck winter tyre for steering axles but is also suitable for trailers.
- The wide tread pattern and the tread pattern with 5 main grooves enable very good and safe handling on snow and ice.
- Jagged sipes increase the contact area with the road and enhance the grip.
- The sipe design and the shoulder grooves open on the sides reliably deflect water and snow.
- The special rubber compound keeps its positive characteristics even at low temperatures.



Technical Informations

Item number	11066388
EAN	6959655469059
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	160 K (158 L), 20 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SAW1
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	Е
Wet grip	С
Rolling noise [db].	74
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	75,93
Recommended rim size	11.75
Permitted rim size	12.25
Maximum air pressure [bar].	9,00
Section width (mm)	385
Outer diameter of tyre [mm].	1072
Stat. radius (SLR) [mm]	496
Rolling circumference [mm].	3103
Tread depth (mm)	15,0

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.





E-Ready	No
---------	----

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 K	4500	110	Single	9,00	
158 L	4250	120	Single	9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.