

TYRES

Product group	Tyres
Item number	11066406
Valid tyre size	425 / 65 R 22.5
LI / SI / PR	165 K, 20 PR
TL/TT	TL
Brand	Sailun
Tread pattern	S825



 **SAILUN**
TYRE

Notes and features

- The Sailun S825 is a truck tyre for all axles.
- The optimised tread compound increases the tyre's service life.
- Its special shoulder design and the wide tread provide good stability.
- Stone ejectors in the circumferential tread ribs prevent tyre damage caused by the penetration of small stones.

Technical Informations

Item number	11066406
EAN	4040658093739
Valid tyre size	425 / 65 R 22.5
LI / SI / PR	165 K, 20 PR
TL/TT	TL
Brand	Sailun
Tread pattern	S825
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	D
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	89,00
Recommended rim size	12.25
Permitted rim size	11.75, 13.00, 14.00
Maximum air pressure [bar].	8,30
Section width (mm)	425
Outer diameter of tyre [mm].	1124
Rolling circumference [mm].	3235
Tread depth (mm)	17,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
165 K	5150	110	Single	8,30	