

## **TYRES**

| Product group   | Tyres           |  |
|-----------------|-----------------|--|
| Item number     | 11066410        |  |
| Valid tyre size | 445 / 65 R 22.5 |  |
| LI / SI / PR    | 169 K, 20 PR    |  |
| TL/TT           | TL              |  |
| Brand           | Sailun          |  |
| Tread pattern   | S696            |  |





## Notes and features

- The Sailun S696 is a truck tyre for trailer axles.
- Its special rubber compound, wide tread and extra wide tyre shoulder enable slow and even wear and thus a long service life for the tyre.
- Small sipes in the tread enable low heat generation and excellent grip in all weather conditions.
- The circumferential zigzag-shaped grooves eject small stones and prevent the tyre from being damaged.



## **Technical Informations**

| Item number                  | 11066410        |
|------------------------------|-----------------|
| EAN                          | 4040658096235   |
| Valid tyre size              | 445 / 65 R 22.5 |
| LI / SI / PR                 | 169 K, 20 PR    |
| TL/TT                        | TL              |
| Brand                        | Sailun          |
| Tread pattern                | S696            |
| M+S                          | M+S             |
| Axle position truck          | TR              |
| Rolling resistance           | С               |
| Wet grip                     | В               |
| Rolling noise [db].          | 72              |
| Antistatic                   | No              |
| Tyre colour                  | Black           |
| ECE regulation number        | ECE 54,ECE 117  |
| Nettogewicht [kg] (gültig)   | 95,01           |
| Recommended rim size         | 13.00           |
| Permitted rim size           | 14.00           |
| Maximum air pressure [bar].  | 9,00            |
| Section width (mm)           | 444             |
| Outer diameter of tyre [mm]. | 1150            |
| Tread depth (mm)             | 15,5            |
| E-Ready                      | No              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 169 K | 5800               | 110          | Single        | 9,00                        |              |