# Bohnenkamp Moving Professionals

#### **TYRES**

Product group	Tyres	
Item number	11066411	
Valid tyre size	445 / 65 R 22.5	
LI / SI / PR	168 K, 20 PR	
TL/TT	TL	
Brand	Sailun	
Tread pattern	S825	



#### Notes and features

- The Sailun S825 is a truck tyre for all axles.
- The optimised tread compound increases the tyre's service life.
- Its special shoulder design and the wide tread provide • good stability.
- Stone ejectors in the circumferential tread ribs prevent • tyre damage caused by the penetration of small stones.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

# Bohnenkamp Moving Professionals

## **Technical Informations**

Item number	11066411
EAN	6959655401615
Valid tyre size	445 / 65 R 22.5
LI / SI / PR	168 K, 20 PR
TL/TT	TL
Brand	Sailun
Tread pattern	S825
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	D
Wet grip	C
Rolling noise [db].	72
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	96,00
Recommended rim size	13.00
Permitted rim size	14.00
Maximum air pressure [bar].	8,30
Section width (mm)	444
Outer diameter of tyre [mm].	1150
Rolling circumference [mm].	3485
Tread depth (mm)	16,5
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 K	5600	110	Single	8,30	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.