

TYRES

Product group	Tyres	
Item number	11066412	
Valid tyre size	445 / 65 R 22.5	
LI / SI / PR	169 K, 20 PR	
TL/TT	TL	
Brand	Sailun	
Tread pattern	S696	





Notes and features

- The Sailun S696 is a truck tyre for trailer axles.
- Its special rubber compound, wide tread and extra wide tyre shoulder enable slow and even wear and thus a long service life for the tyre.
- Small sipes in the tread enable low heat generation and excellent grip in all weather conditions.
- The circumferential zigzag-shaped grooves eject small stones and prevent the tyre from being damaged.



Technical Informations

Item number	11066412
EAN	6959655412697
Valid tyre size	445 / 65 R 22.5
LI / SI / PR	169 K, 20 PR
TL/TT	TL
Brand	Sailun
Tread pattern	S696
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Rolling resistance	С
Wet grip	С
Rolling noise [db].	72
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	95,50
Recommended rim size	13.00
Permitted rim size	14.00
Maximum air pressure [bar].	9,00
Section width (mm)	444
Outer diameter of tyre [mm].	1150
Stat. radius (SLR) [mm]	528.72
Rolling circumference [mm].	3485
Tread depth (mm)	15,5

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



E-Ready No	
------------	--

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 K	5800	110	Single	9,00	