

TYRES

Product group	Tyres
Item number	11085100
Valid tyre size	15.5 R 25
LI / SI / PR	176 A2 / 160 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS300





Notes and features

- The Maxam MS300 is an EM tire for wheel loaders, dumpers, graders and similar vehicles.
- It is ideal for use on sandy or simple surfaces.
- The tyre provides very good traction even when working off-road
- Its thick base rubber layer and the cut and wear-resistant rubber compound provide very good protection against injuries.



Technical Informations

Item number	11085100
EAN	6959655438857
Valid tyre size	15.5 R 25
LI / SI / PR	176 A2 / 160 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS300
TRA Code	E3/L3
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	135,00
Recommended rim size	12.00/1.3
Maximum air pressure [bar].	6,50
Section width (mm)	388
Outer diameter of tyre [mm].	1276
Stat. radius (SLR) [mm]	570
Rolling circumference [mm].	3793
Tread depth (mm)	23,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 A2	7100	10	Loader dozer	6,50	
160 B	4500	50	Transport	5,25	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.