

TYRES

Product group	Tyres
Item number	11085112
Valid tyre size	17.5 R 25
LI / SI / PR	182 A2
TL/TT	TL
Brand	Maxam
Tread pattern	MS503



Notes and features

- The Maxam MS503 is an EM radial tyre for wheel loaders, graders and similar vehicles for versatile applications.
- Its open, particularly deep tread (L5) offers excellent traction and high wear resistance on all surfaces.
- The reinforced bead, tyre shoulder and sidewall as well as the thick base rubber layer protect the tyre from cuts, punctures and other damage.
- The wide and flat contact surface provides stability and ensures slow, uniform wear.
- Special stone and mud deflectors between the studs allow very good self-cleaning.

Technical Informations

Item number	11085112
EAN	6959655430448
Valid tyre size	17.5 R 25
LI / SI / PR	182 A2
TL/TT	TL
Brand	Maxam
Tread pattern	MS503
TRA Code	L5T
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	241,00
Recommended rim size	14.00/1.5
Maximum air pressure [bar].	6,50
Section width (mm)	433
Outer diameter of tyre [mm].	1408
Stat. radius (SLR) [mm]	647
Rolling circumference [mm].	4242
Tread depth (mm)	64,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
182 A2	8500	10	Loader dozer	6,50	