

TYRES

Product group	Tyres
Item number	11085202
Valid tyre size	23.5 R 25
LI / SI / PR	201 A2
TL/TT	TL
Brand	Maxam
Tread pattern	MS501 MINEXTRA





Notes and features

- The Maxam MS501 MineXtra is an EM radial-ply tyre for wheel loaders, dozers and similar vehicles operating under the toughest conditions.
- Its special C.R. rubber compound is exceptionally cut and shock-resistant.
- The deep tread (L5) ensures very good traction and slow wear
- The reinforced bead, tyre shoulder and sidewall as well as the thick base rubber layer protect the tyre from cuts, punctures and other damage.



Technical Informations

Item number	11085202
EAN	6959655425369
Valid tyre size	23.5 R 25
LI / SI / PR	201 A2
TL/TT	TL
Brand	Maxam
Tread pattern	MS501 MINEXTRA
TRA Code	L5
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	511,00
Recommended rim size	19.50/2.5
Maximum air pressure [bar].	6,50
Section width (mm)	608
Outer diameter of tyre [mm].	1662
Stat. radius (SLR) [mm]	740
Rolling circumference [mm].	4932
Tread depth (mm)	80,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
201 A2	14500	10		6,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.