

TYRES

Product group	Tyres
Item number	11085251
Valid tyre size	26.5 R 25
LI/SI/PR	209 A2
TL/TT	TL
Brand	Maxam
Tread pattern	MS503





Notes and features

- The Maxam MS503 is an EM radial tyre for wheel loaders, graders and similar vehicles for versatile applications.
- Its open, particularly deep tread (L5) offers excellent traction and high wear resistance on all surfaces.
- The reinforced bead, tyre shoulder and sidewall as well as the thick base rubber layer protect the tyre from cuts, punctures and other damage.
- The wide and flat contact surface provides stability and ensures slow, uniform wear.
- Special stone and mud deflectors between the studs allow very good self-cleaning.



Technical Informations

Item number	11085251
EAN	6959655430554
Valid tyre size	26.5 R 25
LI / SI / PR	209 A2
TL/TT	TL
Brand	Maxam
Tread pattern	MS503
TRA Code	L5
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	635,17
Recommended rim size	22.00/3.0
Maximum air pressure [bar].	6,50
Section width (mm)	683
Outer diameter of tyre [mm].	1798
Tread depth (mm)	87,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
209 A2	18500	10		6,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.