Bohnenkamp Moving Professionals

20.09.2024

TYRES

Product group	Tyres	
Item number	11166060	
Valid tyre size	315 / 70 R 22.5	
LI / SI / PR	154 / 151 M (156 / 150 M), 20 PR	
TL/TT	TL	
Brand	GoodTrip	
Tread pattern	GHD20	





Notes and features

- The GoodTrip GHD20 is a radial truck tyre for the drive axle.
- The directional tread with rugged tread blocks guarantees very good traction under all weather conditions, even in snow.
- The unique tyre shoulder design with a special rubber compound prevents the tyre from heating up and counteracts tooth-shaped wear.
- Its particularly high tread depth ensures very good traction, even on slippery roads, and a long service life.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	11166060	
EAN	8859625700077	
Valid tyre size	315 / 70 R 22.5	
LI / SI / PR	154 / 151 M (156 / 150 M), 20 PR	
TL/TT	TL	
Brand	GoodTrip	
Tread pattern	GHD20	
M+S	M+S	
3PMSF	3PMSF	
Axle position truck	RA	
Rolling resistance	D	
Wet grip	C	
Rolling noise [db].	75	
Rolling noise level	В	
Antistatic	No	
Tyre colour	Black	
ECE regulation number	ECE 117,ECE 54	
Nettogewicht [kg] (gültig)	61,14	
Recommended rim size	9.00	
Permitted rim size	9.75	
Maximum air pressure [bar].	9,00	
Section width (mm)	312	
Outer diameter of tyre [mm].	1014	
Stat. radius (SLR) [mm]	469	
Rolling circumference [mm].	3209	
Tread depth (mm)	18,5	

20.09.2024

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 M	3750	130	Single	9,00	
156 M	4000	130	Single	9,00	
151 M	3450	130	Twin	9,00	
150 M	3350	130	Twin	9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.